

Bug Deflector Install Guide

(04-08) F150

Contents:

- (1) Bug Deflector
- (2) Push Pins
- (4) Rubber Bumpers
- (1) Alcohol Wipe

Tools Required:

10mm Socket at Ratchet



Step 1//

Begin by raising the hood to access the grille mounting hardware. Remove the (4) 10mm bolts that hold the grille brace to the hood.



Step 2//

Then remove the (4) 10mm nuts that secure the grille to the top of the hood. Carefully Remove the grille from the vehicle.



Step 3//

Thoroughly clean the underside of the hood where the tape backing makes contact with the paint. It is critical that this painted surface is clean of any and all dirt, oil, grease, etc prior to removing the tape backing. Then use the supplied alcohol wipe to remove any remaining contaminants.



Step 4//

Once the paint is clean and dry, remove the tape backing. Install the Bug Deflector with the supplied push clips in the pre-existing holes. Apply firm even pressure on the taped surfaced to ensure proper adhesion.



Step 5//

Install the grille over the installed Bug Deflector. The grille will hold the center portion of the Bug Deflector when the factory nuts are reinstalled. Reinstall all the factory nuts and bolts that secure the grille to the vehicle.

Finish the installation by installing the supplied rubber bumpers to protect the paint anywhere the Bug Deflector may make contact with the hood, typically placed at either end and evenly spaced in the center.