## 15-17 F-150 Mud Guards **Installation Guide**

## Contents:

- (2) Front Mud Guards
- (2) Rear Mud Guards
- (6) Plastic Push Clips
- (6) Metal Clips
- (4) Screw Clips
- (10) Phillips Screws
- (2) Metal Brackets

## **Tools Required:**

- 7/32" Socket
- Phillips screwdriver
- Pry tool



//Step 2:

At the top of the mud guard, fold the tab on the mud guard around the fender. Once folded, install the (2) Phillips screws on the mud guard to secure the guard to vehicle. Then at the folded tab, install (1) metal clip to hold the top of the mud guard to the fender.

\*\*Note: The metal clips are very tight by design.



//Step 4 (Rear):

Remove the (3) push clips. (2) clips are in the wheel well, while (1) clip is under the bed. Do not remove the plastic panel from the vehicle.




// Step 1 (Front):

Remove the (2) 7/32" bolts from the lower fender guard. Do not remove the panel from the vehicle.



//Step 3:

Once the screws and clip is installed, front installation is complete. Repeat procedure to install mud guards to opposite side of vehicle.



//Step 5:

Insert (1) screw clip onto the vehicle [A], then align the mud guard to the vehicle. Insert (2) push pins into the lower portion [B], and install (1) Phillips head screw into the screw clip through the bottom. Then install (2) metal clips above to secure the mud guard [D].

\*\*Note: The metal clips are tight by design.



//Step 6:
Using provided bracket, install the supplied screw clips to the bracket. Using provided Phillips head screws, attach bracket to vehicle as shown. Repeat procedure to install mud guards to opposite side of vehicle.