IMPORTANT: PLEASE RETAIN THIS INSTRUCTION MANUAL FOR FUTURE REFERENCE



2007-09 Chevrolet Silverado 2 Piece **Mesh Grille**

A 29 G7

Notes to the Technician:

E&G is proud to present this package to you and reminds you that for technical information, contact Lynn Eash or Lee Clary at 410-381-4900. Do not attempt installation any E&G product without first reading the detailed instructions. E&G Classics will not warrant damaged parts or vehicle

Copyright © 2007 by E&G Classics, Inc.

All right reserved. The reproduction or utilization of this work in any form or any electronic, mechanical, or other means, no known or hereafter invented, including xerography, photocopying, and recording, and in any information storage retrieval system is forbidden without written permission of owners.




Fine Mesh Part # 1022-0102-07

| Quantity | <u>Description</u> | Part No. |
|----------|--|--------------|
| 1 | Upper Mesh Grille Insert | 1022-002A-07 |
| 1 | Upper Mesh Grille Frame | 1022-0038-07 |
| 1 | Lower Mesh Grille Insert | 1022-002B-07 |
| 1 | Lower Mesh Grille Frame | 1022-0039-07 |
| 1 | Hardware Kit (components listed below)_ | 1022-1902-07 |
| 20 | 1.006" x .189" x .064" Black Plastic Washers | 1999-0264-00 |
| 20 | 8-32 ESNA Half Nuts S.S. | 1999-0065-00 |
| 11 | .156 x 1" Vinyl Caps | 1999-0241-00 |
| | | |

WARNING: Please handle with care. The edges of the STAINLESS STEEL TRIM are EXTREMELY SHARP!

Once the protective liner is peeled off the stainless steel grille sections. E&G recommends wiping the glue residue with a mild solvent on a soft cloth to loosen the remaining glue. Once the glue is removed, use glass cleaner and a solf cloth to remove the solvent residue.



1. Open the hood and remove all the factory push pins securing the cover from the top of the radiator support panel.

due to altered installation instructions.

WARRANTY INFORMATION:

E&G Classics, Inc. warrants its chrome parts and products to be free from defects in material, workmanship or finish for Twenty-Four (24) months from the date of shipment by E&G. This warranty is limited to the repair or replacement, at E&G Classics option, of the defective part or product.


To obtain performance under this warranty you must:

- 1.) Present your E&G unit to an authorized distributor in your area with proof of purchase.
 2.) If no distributor is available, contact E&G Classics (address below) for authorization to return unit.
- 3.) Returns All unauthorized returns will be refused. Merchandise approved by E&G for return must have been purchased witHin the Twenty-Four (24) months. All returns require an authorization number obtained from E&G and the actual return must be accompanied by the written authorization form filled out completely. All merchandise must be inspected upon receipt and shortages reported within 48 hours. All merchandise must be in a resalable condition. Merchandise must be packed carefully in the original packing. If original packing is no longer usable, repack item(s) comparable to original manner. All returns are subject to a 25% handling charge. Special order items are not returnable. Defective merchandise must have an explanation of the problem. No credit will be issued unless invoice number and date of purchase has been supplied. Manufacturer shall be sole judge of defects in a product.
- 4.) UPS accounts All returns must be prepaid. Do not send return shipments freight collect. Once E&G has made its decision and it is a claim against our warranty policy, E&G will credit incoming freight on damaged parts.
- 5.) No discontinued part or parts changed due to body style are returnable.


For Return Authorization, write or telephone: E&G Classics, Inc., 8910 McGaw Court, Columbia, MD 21045 (410) 381-4900 Attn.: Return Department

You are responsible for inspecting all packages containing E&G Classics' parts and product immediately upon their receipt and must file a claim with the carrier for any damage disclosure by such inspection and notify E&G classics in writing at the above address of any such damage. This warranty does not extend to any of our products which have been subject to misuse, neglect, accident or have been altered or repaired in any way. This warranty does not cover any accidental or consequential damages for any breach of this warranty agreement. EGG Classics shall have no responsibility for any loss of time, inconvenience, commercial loss or consequential damage, nor shall EGG be liable for any injury or damage to persons or property by reason of any defect in material, workmanship or finish of its parts or products. This warranty gives you specific legal rights and you may also have other rights which may vary from state to state.


DO NOT USE ABRASIVE CLEANERS OF ANY TYPE ON THE GRILLE.



2. Cut the end from each black silicone sleeve and install one onto the bottom and side studs on the upper and lower grilles prior to vehicle installation (lower shown).




- **3.** Apply masking tape to the factory grille surrounds before aligning the mesh grille and frames to protect the factory arille finish.
- 4. Carefully align the upper and lower grille mesh and frames and use masking tape to secure them while installing the mounting hardware.



Carefully install large black plastic washers and #8-32 ESNA nuts onto the studs and but do not tighten until the protective masking tape is removed from the factory grille frame.



6. Carefully peel off the protective masking tape from the factory grille frame (pull it back over itself as shown to minimize breakage, you can also shift the mesh grille sections to create additional clearance).



- Tighten the mounting hardware. IMPORTANT: Do not overtighten the #8-32 ESNA lock nuts or you will indent the grille where the studs are welded.
 Reinstall the radiator cover removed in Step 1.



Finished installation.