



## Ford F150 (2004-2008)

### 4" Bull Bar

#### Contents:

- |                              |                         |
|------------------------------|-------------------------|
| (1) - Bull Bar               | (6) - 3/8" Hex Nut      |
| (1) - Driver side bracket    | (2) - M10 Hex Head Bolt |
| (1) - Passenger side bracket | (2) - M10 Flat washer   |
| (4) - Bolt Plates            | (2) - M10 Lock washer   |
| (4) - 1/2" Flat washers      |                         |
| (4) - 1/2" Lock washers      |                         |
| (4) - 1/2" Nut               |                         |
| (6) - 3/8" Hex Head Bolt     |                         |
| (12) - 3/8" Flat washers     |                         |
| (6) - 3/8" Lock washers      |                         |

#### Tools Needed:

15mm, 16mm, 18mm Wrenches and Sockets



Left side for vehicles with factory tow hooks,  
Right side without factory tow hooks.



#### Vehicle with Tow Hooks

If equipped with tow hooks, remove factory tow hooks. Be careful to keep the bolt plate aligned in the frame.



Loosely attach bar brackets to the frame rails. Mount the Bull Bar to the frame brackets securely. Then finish torquing brackets to the frame rails.



#### Vehicle without Tow Hooks

Insert two bolt plates through the end of the frame and into bottom frame holes. \*\*Note: It may be necessary to remove the lower plastic portion of the bumper to gain access to ends of the frame rails.



Level and adjust Bull Bar as desired.

Torque tow hook bolts to 75ft lbs.  
1/2" Fasteners to 65ft lbs.  
10mm fasteners to 35ft lbs.  
3/8" fasteners to 30ft lbs.